





Vero Series

External Lighting



Recessed wall light for walkways, pathways, steps, etc. available in 4 versions.

Construction: Die-cast aluminium housing. IP65.

Installation: Separate In-Housing required for Installation.

Lens: Tempered prismatic glass, 3mm.

Finish: Light grey finish as standard. Anthracite grey on request.

LED: 3.5w -10w LED. 4K as standard, 3K on request.

Driver: Internal.


Options: DALI, RAL colours on request.

Product Compliance: EN 60598, CE.




DIMENSIONS


Size 1




Size 2







Size 3



Size 4



All dimension in mm.



ORDERING CODES

Wattage	Type	Size	Code	Details	+Installation Frame	Lumens*
3.5w	LED	1	G-5410.ALX.P	4K, LED Driver Internal	G-003 (L144 x W87 x D132)	450 lm
10w	LED	2	G-5406.ESX.P	4K, LED Driver Internal	G-406 (L226 x W188 x D110)	1340 lm
7w	LED	3	G-5409.ESX.P	4K, LED Driver Internal	G-002 (L268 x W144 x D98)	900 lm
10w	LED	4	G-5408.FHX.P	4K, LED Driver Internal	G-002 (L268 x W144 x D98)	1330 lm

*Source lumens

OPTIONS

3K: 3000K, Warm White
.05: Anthracite Grey Finish
.13: Light Grey Finish
DALI: DALI on request