



Akkor Wand

Solar lighting



Square Profile Aluminium Mast with integrated Solar Panels, Lighting system and a choice of other features.

Construction: Aluminium, square Profile, Flanged as standard. Available in 2 Heights 4m or 6m. IK10.

Lighting: Integrated LED Light with clear polycarbonate Lens. Option of 2nd Light on 6m version (which would bring Height to 6.5M. IP66. IK08.

Finish: Black RAL 9006 as standard. Other RALs on request.

LED: Each Light unit 25w 16LED max. 4K as standard, 3K on request.

Solar Panel: Monocrystalline, 100w/200w (50w or 100w Per Side, Max 2 sides).

Battery: 12.8/25.6 V - 300 to 1300 Wh. Located in Base of Pole.



Options: Number of Solar Panels, LED Light units, Height, Wattages/ beam angles, RAL Finish.

Manufactured: EU.

Product Compliance: EN 60598; CE.

DIMENSIONS

Weight:
 4m Version: 50 Kgs
 6m Version: 65 Kgs



ORDERING CODE

| Solar Panel | LED * Watt | Type | Height | Code | Description | Lumens |
|-------------|------------|-------|--------|-----------|--|---------|
| 100w | 10w | 16LED | 4.0m | 5AKK4025A | Akkor Wand, 2 Solar Sides, 1 Light unit, 4k | 1600 lm |
| 200w | 10w | 16LED | 6.0m | 5AKK6025A | Akkor Wand, 2 Solar Sides, 1 Light unit, 4K | 1600 lm |
| 200w | 10w | 16LED | 6.0m | 5AKK6025B | Akkor Wand, 2 Solar Sides, 1 Light unit, 4K | 1600 lm |
| 200w | 20w | 16LED | 6.6m | 5AKK6650B | Akkor Wand, 2 Solar Sides, 2 Light units, 4K | 3200 lm |

OPTIONS

3K: 3000K, Colour Temperature

MS: Motion Sensor

RAL: Please specify

* Only 10w LED optical unit shown. Other wattages include 25w and 40w.